




Material

Part	Material
Cap And Body	TENSILE CAST IRON FC22
Valve Seat	HEAT TREATED CHROME STEEL
Valve	HEAT TREATED CHROME STEEL
Gasket	COMPRESSED NON-ASBESTOS
Lever	SUS 304
Valve Retainer	SUS 304
Bucket	STAINLESS STEEL SUS 304
Integral Strainer	STAINLESS STEEL SUS 304
Water Hammer Resister	STEEL

สตีมแทร็ปบัคเก็ต(รูปถ้วย) เหล็กหล่อเกลียว

When placing order of steam trap, please indicate with:

1. Model number.
2. Dimension of pipe connection: Screwed end: BSPT
3. Specify type of flanged in detail: Flanged end: JIS 10K
4. Operating pressure setting: 3K / 5K / 10K / 14K / 18K. (Maximum: 18 kg/cm²)



Screwed Type

Model	Connection	L	H	H1	A	Weight (kg)	M.O.P. kg/cm ²
B1	1/2", 3/4", 1"	128	100	175	96	3.5	18
B2	3/4", 1"	168	133	228	144	7.2	18
B3	1"	198	173	296	178	13.5	18
B4	1.1/4", 1.1/2"	232	185	347	203	21	18

CONNECTION: BSPT,