





CAST IRON / DUCTILE IRON WAFER TYPE DUAL-PLATE CHECK VALVE

ISO 9001

MODEL: WCV-12U / WCV-124 /

เวเฟอร์เช็ควาล์วเหล็กหล่อ/ลึนทองเหลือง/ลึนสแตนเลส

10K/PN10 (ปีกผีเสื้อ)



1. Design: API-594.
2. Face to Face: EN558-1 Serial 50.
3. Inspection: API-598 & ISO 5208.
4. Suit for: ASME & ISO & JIS.

Material

Part	Model No.	WCV-12U (2"-2-1/2", 3", 4", 6", 8", 10", 12")	WCV-124 (3"-8")
Body		CAST IRON / FCD	CAST IRON / FCD
Plates		BRONZE	SUS 304
Spring		SUS 316	SUS 316
Seat		NBR - EPDM / METAL	NBR - EPDM / METAL

Dimension

Size	Pressure	Ø A	Ø B	C	Dia of Bolt	Stud Selection	Stud	Weight	
inch	Rating	(mm)	(mm)	(mm)	Circle	Stud No.	Stud Dia.	Length (kgs)	
2"	10K	101	60	54	120.0	4	M16	140	2.0
	125LBS	105			120.6	4	5/8"	120	2.0
	PN10 / 16	105			125.0	4	M16	140	2.0
2.1/2"	10K	121	73	54	140.0	4	M16	150	2.5
	125LBS	124			139.7	4	5/8"	120	2.5
	PN10 / 16	124			145.0	8	M16	150	2.5
3"	10K	131	89	57	150.0	8	M16	155	3.0
	125LBS	137			152.4	4	5/8"	120	3.0
	PN10 / 16	137			160.0	8	M16	155	3.0
4"	10K	156	114	64	175.0	8	M16	160	4.5
	125LBS	175			190.5	8	5/8"	140	5.0
	PN10 / 16	156			180.0	8	M16	160	4.5
5"	10K	187	141	70	210.0	8	M20	165	5.5
	125LBS	197			215.9	8	3/4"	150	6.0
	PN10 / 16	187			210.0	8	M16	165	6.0
6"	10K	217	168	76	240.0	8	M20	180	7.5
	125LBS	222			241.3	8	3/4"	165	8.0
	PN10 / 16	217			240.0	8	M20	180	8.0
8"	10K	267	219	95	290.0	12	M20	215	15.0
	125LBS	279			298.4	8	3/4"	185	16.0
	PN10 / 16	267			295.0	8 / 12	M20	215	16.0
10"	10K	330	274	108	355.0	12	M22	235	25.0
	125LBS	340			362.0	12	7/8"	210	26.0
	PN10 / 16	330			350.0 / 355.0	12	M20 / M24	235	25.0
12"	10K	375	324	143	400.0	16	M22	280	45.0
	125LBS	410			431.8	12	7/8"	245	47.0
	PN10 / 16	375			400.0 / 410.0	12	M20 / M24	280	45.0 / 46.0