




DUCTILE IRON LIFT CHECK VALVE CLASS 10K

ISO 9001



| Dimension | | mm | | | | | |
|-----------|------|-----|-----|----|-------|-------|-----|
| Size | inch | 1/2 | 3/4 | 1 | 1.1/4 | 1.1/2 | 2 |
| | mm | 15 | 20 | 25 | 32 | 35 | 50 |
| L | | 65 | 80 | 90 | 105 | 120 | 140 |
| H (open) | | 47 | 54 | 55 | 67 | 78 | 83 |

* The available Thread: BS21

DG-162 Below 120°C 14 kgf/cm²
 (SUS Disc) Below 220°C Steam, Air, Gas, Oil 10 kgf/cm²

Test Pressure


Body 24 kgf/cm² (Hydrostatic)
 Seat 15 kgf/cm² (Hydrostatic)
 6 kgf/cm² (Air)

ลิฟท์เช็ควาล์วเหล็กดักไหลย้อนกลับ 10K / 16K (ชื่อรุ่นเดิม TC-16)

Material

| | |
|----------------|---------------|
| Model | DG-162 |
| Body | FCD |
| Cap | SUS 410 / FCD |
| Disc | SUS 410 |
| Body Seat Ring | SUS 410 |
| Spring | SUS 304 |

DUCTILE IRON LIFT CHECK VALVE CLASS 20K



| Dimension | | mm | | | | | |
|-----------|------|-----|-----|-----|-------|-------|-----|
| Size | inch | 1/2 | 3/4 | 1 | 1.1/4 | 1.1/2 | 2 |
| | mm | 15 | 20 | 25 | 32 | 40 | 50 |
| L | | 75 | 90 | 105 | 120 | 135 | 160 |
| H | | 55 | 57 | 63 | 70 | 78 | 86 |

* The available Thread: BS21

DG-202 Below 120°C 28 kgf/cm²
 (SUS Disc) Below 220°C Steam, Air, Gas, Oil 25 kgf/cm²
 300°C Steam, Air, Gas, Oil 23 kgf/cm²
 350°C Steam, Air, Gas, Oil 20 kgf/cm²

Test Pressure

Body 44 kgf/cm² (Hydrostatic)
 Seat 32 kgf/cm² (Hydrostatic)
 6 kgf/cm² (Air)

ลิฟท์เช็ควาล์วเหล็กดักไหลย้อนกลับ 20K (ชื่อรุ่นเดิม TC-20)

Material

| | |
|-------------|----------------|
| Model | DG-202 |
| Body | FCD |
| Bonnet | SUS 410 / FCD |
| Disc | SUS 410 |
| Bonnet Ring | SUS 410 |
| Seat Ring | SUS 410 |
| Gasket | ASBESTOS SHEET |
| Spring | SUS 304 |