




DUCTILE IRON LIFT CHECK VALVE CLASS 10K

ISO 9001



Dimension		mm						
Size	inch	1/2	3/4	1	1.1/4	1.1/2	2	
	mm	15	20	25	32	35	50	
L		108	117	127	140	165	203	
H (open)		55	55	63	68	80	88	

* End Flanged Dimensions to JIS 10K.

DG-112	Below 120°C	14 kgf/cm ²
(SUS Disc)	Below 220°C Steam, Air, Gas, Oil	10 kgf/cm ²

Test Pressure


Body	24 kgf/cm ² (Hydrostatic)
Seat	15 kgf/cm ² (Hydrostatic)
	6 kgf/cm ² (Air)

ลิฟท์เช็ควาล์วเหล็กดักไหล หน้าแปลน 10K/16K (รุ่นเดิม TCF-16)

Material

Model	DG-112
Body	FCD
Bonnet	SUS 410 / FCD
Disc	SUS 410
Bonnet Ring	SUS 410
Gasket	ASBESTOS SHEET
Seat Ring	SUS 410
Spring	SUS 304

DUCTILE IRON LIFT CHECK VALVE CLASS 20K



Dimension		mm						
Size	inch	1/2	3/4	1	1.1/4	1.1/2	2	
	mm	15	20	25	32	40	50	
L		110	120	130	160	180	230	
H		55	60	63	68	80	88	

* End Flanged Dimensions to JIS 20K.

DG-208	Below 120°C	28 kgf/cm ²
(SUS Disc)	Below 220°C Steam, Air, Gas, Oil	25 kgf/cm ²
	300°C Steam, Air, Gas, Oil	23 kgf/cm ²
	350°C Steam, Air, Gas, Oil	20 kgf/cm ²

Test Pressure

Body	44 kgf/cm ² (Hydrostatic)
Seat	32 kgf/cm ² (Hydrostatic)
	6 kgf/cm ² (Air)

ลิฟท์เช็ควาล์วเหล็กดักไหล หน้าแปลน 20K (รุ่นเดิม TCF-20)

Material

Model	DG-208
Body	FCD
Bonnet	SUS 410 / FCD
Disc	SUS 410
Bonnet Ring	SUS 410
Gasket	ASBESTOS SHEET
Seat Ring	SUS 410
Spring	SUS 304